

Power Line Communication

HP-F670 - HomePlugPass Through

Franch 6AC outlet Surge Protector

L-N, L-G, N-G Surge Protection

Power Cord:H05VV-F 3G 1.0MM 1M

HomePlug AV with 3 port Ethernet



HP-F670

Safety Approval



Features

- ◆ No new wires, just plug in AC outlet and data will be transmitted in power lines.
- ◆ AC power line surge protector. Protect high-tech electronic devices from damage caused by dangerous spikes/surges that coming from AC power line.
- ◆ Safety shutter, avoid direct touch of live parts in the outlet by accident. Safe for the children.

Specification

Features	HP-F670
Power Rating	16A, 250VAC
Outlet Type	FRANCH OUTLETS
No. of Outlet	6 AC OUTLETS
Plug Type	GERMAN/FRANCH
Power Cord	H05VV-F 3G 1.0MM, 1M
AC Surge	L-N, L-G, N-G SURGE PROTECTION
EMI/RFI Filter	NIL
Switch	YES
Indicator	*SURGE INDICATOR*POWER ON STATUS INDICATOR
Safety Shutters	YES
Computer	IEEE802.3IEEE802.3u
Network Interface	*Three RJ-45(10/100Bass-T Ethernet)*One 200Mbps Power Line supporting coexistence with 14/85Mbps HomePlug
Standard	HomePlug AV
Access	*Mix of TDMA and CSMA/CA channel access scheme;*CO device generates a periodic beacon carrier for channel access scheme
Nodes	8 nodes Max.
Data Transfer Rate	200Mbps over Powerline and 10/100Mbps over Ethernet
Frequency Band	2~28Mhz
Quality of Service	YES
Encryption	128bit AES
Modulation Type	OFDM Symbol Modulation on Line synchronization1024/256/64/16/8-QAM, QPSK, BPSK, ROBO Carrier Modulation

AHOKU ELECTRONIC COMPANY

5F, NO.88, Sec.1, Nei-Hu Rd., Taipei, Taiwan

TEL:886-2-27991199 FAX:886-2-27999099

Copyright © AHOKU Electronic Company. All Rights Reserved