

Power Line Communication

HP-071A0-085 - HomePlugEthernet Bridge

HomePlug Turbo Ethernet Bridge Adapter

Safety Approval



HP-071A0-085

Feature



No new wires, just plug in AC outlet and data will be transmitted in power lines.

Specification

Model No.	HP-071A0-085
Power Rating	100-240V0.2A
Outlet Type	USA
No. of Outlet	NIL
Plug Type	USA PLUG
AC Surge Protection	NIL
EMI/RFI Filter/Switch	NIL
Safety Shutters	NIL
Indicator	PL-Link/Act; ETH-Link/Act
Weight / Size	150G / 96X70X32
Computer Interface	IEEE802.3IEEE802.3u
Network Interface	85Mbps Powerline Port/10BASE-T/100BASE-TX Ethernet Port
Standard	HomePlug 1.0 Turbo
Additional Protocols	Forward Error Correction(FEC)/Automatic Channel Adaptation
Nodes	8 nodes Max.
Data Transfer Rate	85Mbps over Powerline and 10/100Mbps over Ethernet
Frequency Band	4~21Mhz
Quality of Service	YES
Encryption	56bit DES
Modulation Type	OFDM Symbol Modulation DQAM256/64/16-QPSK, DBPSK, ROBO Carrier Modulation

AHOKU ELECTRONIC COMPANY

5F, NO.88, Sec.1, Nei-Hu Rd., Taipei, Taiwan

TEL:886-2-27991199 FAX:886-2-27999099

Copyright © AHOKU Electronic Company. All Rights Reserved