

## QC 2.0/3.0 Travel Adapter

### EEC-148QC-24 - QC 3.0 USB Travel Adapter

EEC-148QC-24 integrates Quick Charge 3.0 and BC 1.2 Fast Charge function with multi-national plugs and USB charger in a compact size convenient for user to connect power while travelling over the world. The Quick Charge even can reduce charging time to 80%.

The USA/AUS/UK/EU plugs adapt the electric appliances to different countries power socket.

The USB charger with 2.4A capacity can charge the smart phones, tablets, digital cameras and other 3C electronic products equipped USB interface.



EEC-148QC-24

#### Safety Approval :



#### Features

- ◆ Feature Built-in multi-nation plugs can be selected to fit wall outlets in different countries. Perfect for your appliances in oversease travel.
- ◆ International patented safety locking and plug-out mechanism design.
- ◆ Ingenious! Stylish! Light weight! Compact! Easy to carry! Use in anywhere! Anytime! Perfect for travelling.
- ◆ USB charger, ideal for use with iPad( 2,000/1,000mA charger only), iPhone, iTune, iPod, mobile phone, MP3, GPS
- ◆ All-in-One integrated design. Universal plugs + Universal outlet + USB charger.
- ◆ Built-in fuse for overload protection.
- ◆ AHOKU International Patents.
- ◆ Build-in detector IC support BC1.2 / Apple / Samesung charging devices.
- ◆ Compliant with QC2.0 specification. Support 5V/9V/12V charging voltage.

#### AHOKU ELECTRONIC COMPANY

5F, NO.88, Sec.1, Nei-Hu Rd., Taipei, Taiwan  
TEL:886-2-27991199 FAX:886-2-27999099

Copyright © AHOKU Electronic Company. All Rights Reserved

## Specification

<b>Model No.</b>	<b>EEC-148QC-24</b>
<b>Power Rating</b>	6A max. 100-240VAC
<b>Outlet Type</b>	Universal
<b>Plug Type</b>	USA/EUROPE/UK/AUSTRALIA
<b>Surge Protection</b>	Optional
<b>Indicator</b>	YES
<b>Fuse Protection</b>	YES
<b>Safety Shutters</b>	YES
<b>Size</b>	L66 x W48 x H56mm
<b>Weight</b>	113g
<b>USB Charger</b>	5VDC, 2.4A
<b>Fast Charge</b>	QC3.0(3.0A @ 3.6V ~ 1.0A @ 12V)/QC2.0 ( 2.4A @ 5V / 1.4A @ 9V / 1.0A @ 12V ~ 1.0A @ 12V)/BC1.2 (2.4A @ 5V )
<b>Wattage</b>	660W Max. at 110VAC, 1380W Max. at 230VAC

### AHOKU ELECTRONIC COMPANY

5F, NO.88, Sec.1, Nei-Hu Rd., Taipei, Taiwan

TEL:886-2-27991199 FAX:886-2-27999099

Copyright © AHOKU Electronic Company. All Rights Reserved